



AGIP PERMANENT SPEZIAL

AGIP PERMANENT SPEZIAL is a coolant, based on ethylene glycol with innovative corrosion protection (OAT, Organic Acid Technology) which allows for prolonged change intervals (Long-life).

The product is easy-use for direct application, i.e. without dilution with water, as a coolant in the radiator systems of all types of motorcycles. To obtain the full advantages of the high performance of this product, it is advisable not to mix it with other types of antifreeze.

CHARACTERISTICS (TYPICAL FIGURES)

AGIP PERMANENT SPEZIAL

Color	-	Pale red-violet
Boiling point	°C	110
Freezing point	°C	-40
Ph	-	8,0
Mass Density at 15°C	kg/l	1,071

PROPERTIES AND PERFORMANCE

- Formerly addressed to satisfy the needs of motorcycles applications, AGIP PERMANENT SPEZIAL is now one of the most modern radiator protection products on the market capable also to fully meet the performance requirements of passenger cars, heavy-duty vehicles, agriculture and earth-moving machineries, etc.
- It shows a long-term-protection against corrosion for all used materials in the engine and radiator manufacturing, e.g. cast iron, aluminium, copper and solder alloys, as well as good compatibility with tubes, sealing and plastics.
- It contains carefully selected silicate, amine, nitrite, boron and phosphate free inhibitors and is therefore environmental friendly.
- The product is compatible with coolants of previous technology, however, to obtain the full advantages of the high performance of this product, it is advisable not to mix it with other types of antifreeze.



AGIP PERMANENT SPEZIAL

SPECIFICATIONS

AGIP PERMANENT SPEZIAL is officially approved or meets the requirements of the following specifications:

- VW/AUDI/SEAT/SKODA TL 774 D/F (G12/G12+)
- MB 325.3
- MAN 324 tipo SNF
- FORD WSS-M97B44-D
- DEUTZ 0199-99-1115/2091
- OPEL GM 6277M
- RENAULT RVI 41-01-001/Q tipo D
- FVV Heft R443
- O-Norm V 5123
- NATO S-759
- BS 6580
- ASTM D 3306
- ASTM D 4656
- ASTM D 5345
- CUNA NC 956-16

Approved by:

